

NORSOK M-710 Ed. 3 Declaration

A leading independent Test House has assessed with Test Report C6406-2 that:

PTFE G415

is in compliance to the **NORSOK M-710** Ed. 3 -Sept. 2014 – "Qualification of non-metallic sealing materials and manufacturers - Polymers" -Sour Aging Test for both Volume swell and Tensile properties in following conditions:

Exposure conditions

Test temperature (°C)	Sampling intervals (days)
200	
210	2*, 7, 14, 28, 42, 56
220	

Fluid phase distribution

Volume (%)	Composition
30	10% H ₂ S 5% CO ₂ 85% CH ₄
10	Distilled water (conductivity < 5 μS)
60	70/20/10 vol% heptane/cyclohexane/toluene

Marca Nacara

Castelli Calepio, 18th July 2025

Marco Nocera
Quality & Customer Care Mgr.

Note

NORSOK M-710 is a standard for thermoplastics in environments simulating those found in oil & gas production. The standard is widely used by the Oil and Gas industry in screening and selection of polymeric materials for oilfield applications, including sour (hydrogen sulfide) service.

Exposures were performed in the NORSOK standard sour service test fluid: this contains a mixture of liquid hydrocarbons with methane, carbon dioxide and hydrogen sulfide in the gas phase. A range of temperatures up to 220°C were used. NORSOK M710 provides a standardised test method for comparing material performance in conditions simulating a sour oilfield environment.

It does not guarantee suitability for any particular service application. Users should take expert advice when choosing materials.





GUARNIFLON SPA (Società Soggetta all'attività di direzione e coordinamento ex art. 2497 bis C.C. da parte di Mazza Holding S.p.A.)

Sede Legale
Via Soave 7 - 20135 Milano (Mr) TRALY
VAT N. ITO1406020162 - C.F. 01405020162
REG. IMPRESE DI MI - REA 2726062
CAPITALE SOCIALE FOLIO00.000 INTERAMENTE VERSATO
Sede Operativa
Via 1. Tenero et 12 - 24000 Certali III. Calesia (PG) Living

www.guarniflon.com - info@guarniflon.com UE 2018/851 : https://www.guarniflon.com/it/imballaggi





