

DECLARATION

GERMAN CLEAN ACT - VDI GUIDELINE 2440 -

TA LUFT

PAGE 1 OF 1

Date: December 2025

We hereby confirm that representative samples of

Rev. 2

SC 1600

was verified by an accredited laboratory (Test Report No. 3030001) in a first-time test under the following conditions:

Initial gasket stress: 30.7 MPa
related to DN40/PN40: 30.3 MPa
Temperature of exposure: 150 °C
Period of exposure: 48 h.
Remaining gasket stress: 6.3 MPa
Test pressure (absolute): 1 bar
Period of leakage measurement: 24 h.

The leak rate measured with the Helium leak detector at the end of the period of the leakage measurement was :

1.5 · 10⁻⁶ mbar·l/(s⋅m)

Therefore the gasket is in compliance with the tightness criteria of VDI 2440. If the design of the sealing system can be expected to permit normal function in the long term in the given operating conditions and the characteristic sealing value as per DIN 28090-1 or EN 13555, respectively, are observed when choosing and dimensioning the flange connection, the gasket can be regarded as a high-grade sealing system for the purposes of TA-Luft.

Notes

It is the responsibility of the buyer to assure traceability of the material during any further downstream use up to and including the finished machined part as well as the equipment in which it is assembled.

Rev. 0 - Released in January 2016 Rev. 1 – Change in VDI norm Rev. 2 – Declaration updated

MN/jun. 2016





GUARNIFLON SPA

(Società Soggetta all'attività di direzione e coordinamento ex art. 2497 bis C.C. da parte di Mazza Holding S.p.A.)

Sede Legale

Via Soave 7 - 20135 Milano (MI) ITALY
VIA TN. IT01406020162 - C. F. 01406020162

REG. IMPRESE DI MI- REA 2726605
CAPITALE SOCIALE €10.000.000 INTERAMENTE VERSATO
Sede Operativa
Via T.Tasso n° 12 - 24060 Castelli Calepio (BG) ITALY
REG. IMPRESE DI BG - REA 20233







